

GAP SAND



Cement Australia's Gap Sand is a special blend of graded fine sands and additives designed to help lock into place all types of brick and block paving.

SANDS TO SUIT



Directions For Use

1. Lay pavers as per manufacturer's instructions;
2. Gap Sand should be thoroughly swept into all joints using a stiff broom. Ensure that pavers are dry and free from all moisture as any dampness will restrict the free flow of filler into the joint;
3. When all joints are filled a vibrating compactor or similar piece of equipment should then be worked over the entire area of paving to assist the flow of filler into the joints and to ensure the joints are firm;
4. Thoroughly sweep the paved surface, topping up where necessary and remove all excess surface sand;
5. Mist spray the paved surface ensuring that all areas receive a thorough wetting. Avoid heavy spraying or flooding of areas;
6. When Gap Sand is dry and firm, paving is ready for traffic.

Applications

Gap Sand can be used with all types of paving and is ideal in areas of heavy traffic movement, high wind areas, driveways, pool surrounds, sloping sites and for topping up existing paving.

Features & Benefits

- Gap Sand inhibits weed growth and insect infestation by forming a firm but pliable joint between each paver which allows slight movement without distortion or cracking.
- When re-wet through rain or hosing Gap Sand forms a pliable Gel which returns to the firm bond between the pavers once it is dry.
- Assists in maintaining joint integrity and stability
- Quick and easy to use

Availability

Product available in 20kg bags

Limitations

- Gap Sand is not a cement based product and therefore does not stay permanently firm like concrete.
- When Gap Sand is wet from either hosing or rain, or from dampness raising from the sub base, it is soft and pliable and reacts like wet sand, albeit a little 'stickier'.
- Only when it is completely dry does Gap Sand form a firm bond between the pavers.
- Care should be taken whenever paving is hosed not to point the water stream directly into the gaps as this will dislodge wet sand.
- Gap Sand is not recommended for use in paving where the gaps are greater than 3mm wide. Cement Australia's Sand & Cement, swept in dry or mixed wet, is recommended for paving with gaps wider than 3mm.

**For further information on Gap Sand please contact Cement Australia Packaged Products:
Tel: 1300 CEMENT (1300 236 368) Fax: 1800 CEMENT (1800 236 368) www.cementaustralia.com.au**

Specification

- Maximum gap width 3mm
- Maximum particle size 2mm
- Set characteristics – Gel
- Curing time is dependent upon climate and moisture level in pavers

Coverage

One 20kg bag covers approximately 3.5 square metres at a 3mm gap (brick shaped pavers).

Things You Might Need

- Stiff broom
- Hose with 'mist' spray nozzle
- Vibrating compactor

Storage, handling & safety

- Care should be taken when lifting bagged products as personal injury may occur. It is suggested that when lifting bagged materials, the load is shared with another person.
- Gap Sand should be stored in a dry place, off the ground and be protected from ingress of moisture.
- The recommended shelf life is approximately 6 months from date of manufacture. This is provided the product is stored as recommended above. Once opened, the bag must be used on that day.
- For detailed safety information, refer to Cement Australia's Gap Sand Material Safety Data Sheet (MSDS).

Note: The MSDS is available at www.cementaustralia.com.au

Product Disclaimer

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all warranties and conditions implied by statute or otherwise. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

Cement Australia Pty Limited

ABN 75 104 053 474

12 Station Avenue
Darra Queensland 4076
Tel: 1300 CEMENT (1300 236 368)
www.cementaustralia.com.au